

THAW CABINET 1 DOOR - TEMP. -2/+20 °C

Model: SCATGN2



Technical/functional Characteristics

- Inside and outside finishing in AISI 304, 18/10 stainless steel
- 60 mm CFC and HFC-Free high density polyurethane insulation (42 kg/m³)
- Ergonomic full length door handle
- Magnetic gaskets on four sides Ø 2" stainless steel adjustable feet (H 150/180 mm)
- Self closing door with still position at 100°
- Slot-in type supports for containers/shelves easily extractable to foster cleanability
- Air duct for distributing softly the warm air during the defrost cycle and cold air during refrigeration phase
- Refrigeration unit installed on a monoblock structure, removable, and outside evaporator for maximum capacity of the cabinet

TECHNICAL DATA

DIMENSIONS	
WIDTH (MM)	740
DEPTH (MM)	910
HEIGHT (MM)	2070
CAPACITY (LT)	820
CABINET DIMENSIONS (MM)	530x650x1350

TEMPERATURE	-2 / +20
ELECTRIC CONNECTION (V~/HZ)	230
THAWING CAPACITY (Kg)	70 in 5 hours
REFRIG. CAPACITY (*)	506
ELECTRIC POWER (KW)	1800

(*) Evap. temp. -10°C, Cond. temp. +45°C

ACCESSORIES

COUPLE OF SLIDES FOR GRIDS

S/S GRID DIM. 530 X 650 MM

KIT WHEELS