

2G1PE1E

6 EL.ROUND PLATES ON 2/1EL.STATIC OVEN AND CABINET



RANGE FEATURES

- Top: 18-10 stainless steel (12/10 mm gauge)
Free-standing structure with top, front panels, sides and control consoles in 18-10 stainless steel; back panels in stainless steel.
Top, sides, back, front panels and control consoles with satin scotchbrite finish.
Side-by-side top configurations with secure fixing between units.
IPX5 protection rating on all units.
CE approval of all gas products.



FUNCTIONAL FEATURES

- Worktop with recess for collection of juices and cooking plate.
- Nr.6 cast iron round electric cooking plates with internal safety thermostat; plates sealed to worktop.
- Power controlled by 7-position switch.
- Safety thermostat mounted in cooking plates to prevent overheating when operating without product.
- Heat-resistant knobs with screen printed markings and reference index printed on control console.
- Back slot with perimeter edge with enamelled guard.
- Static electric oven for 2/1 GN with AISI 430 stainless steel chamber; insulated with glass wool cladding. Stainless steel container frame with three height levels; removable for cleaning. 1x2/1GN stainless steel chromium plated grid supplied. Removable RAAF FE410D stainless steel oven sole with removable disc for check. Stainless steel inner door to guarantee optimal heat sealing and fitted with heat resistant handle. Useful oven clearance (WxDxH): 53,5x65x30 cm. Control panel with thermostat for temperature control from 80°C to 300°C and different heating configurations: lower elements or upper elements without thermostatic control.
- Ambient compartment, with double-wall door, for 1/1 GN containers, equipped with 4 stainless steel grid guides (clearance between guides 73 mm) and heated by radiating heat. Useful oven dimensions (LxDxH): 33,5x65x40 cm.
- Height adjustable floor-mounted feet in 18-10 stainless steel - floor clearance 180 mm, with non-scratch sole in insulating plastic material.



TECHNICAL FEATURES

- 2 electric plates Ø 220 mm each; available heated surface 3.8 dm², heating power: 2,6 kw each.
- 2 electric plates Ø 180 mm each; available heated surface 2.5 dm², heating power: 2 kw each.
- Three heating elements in AISI 321 stainless steel for total power of 5.2 kW.
- Access to all parts through control panel, easily removable.

Width	Cm	105		
Depth	Cm	70	Electric Power	kW 19,2
Height	Cm	90		
Net weight	Kg	85	Standard connection	V-Hz 400V 3N ~ 50 ÷ 60 Hz