

Pico - Picomatic

Table top slicers

Models

Pico 450
Pico 450 M
Picomatic 450
Picomatic 450 M



PICO

PICOMATIC

- Stylish
- Economical
- Compact, front-loading design

Pico
TABLE TOP SLICER

up to 200 loaves/hour

Picomatic
AUTOMATIC SLICER

up to 200 loaves/hour

Pico is a very ergonomic table-top slicer thanks to its front loading system. Its compact size and attractive design make it ideally suited for incorporation into existing furniture. The automatic **Picomatic** version is even more compact and ergonomic. For breads of a sticky consistency, you can choose from the **'Misch'** versions which are fitted with blade lubrication systems. Auto-start rear cover. Optional base with storage. Colour option also available.

Information screen
Indicates when to change the blades and on 'M' lubrication machines, when to refill with food-safe lubricant.

→ Standard on PICOMATIC

Intelligent Slicing Concept
A system for continuous automatic management of slicing depending on the consistency of the bread. Allows for the slicing of light, crusty or dense breads without operator input.

→ Standard on PICOMATIC

Safety cover
Starts the machine up and opens automatically once slicing is over.
Optional on PICO, standard on PICOMATIC

«M» System

Blade lubrication system
for slicing breads of a sticky consistency. Developed by JAC, it uses a minimal amount of lubricant (120 ml/1,000 loaves) and ensures a clean slice.

→ Optional on PICO and PICOMATIC in three-phase 400 V



Thermoformed drawer
made from a highly-resistant technopolymer with 7-litre crumb capacity.



OPTION: Wheeled base
Sturdy, with a shelf for bags. Height: 62 cm

JAC Flaps
made from a high density technopolymer keep the loaf intact after slicing and facilitate handling.

	PICO 450	PICO 450M	PICOMATIC 450	PICOMATIC 450M
CHARACTERISTICS				
Max. dimensions of loaf (L x W x H) (in cm)	44 x 30 x 18	44 x 29 x 18	44 x 30 x 18	44 x 29 x 18
Power output in single or three-phase 230V / three-phase 400V	0,49 Kw	Three-phase 1,5 Kw 400V	0,49 Kw	Three-phase 1,1 Kw 400V
Net weight (in kg)	105	115	105	115
ADJUSTABLE SETTINGS				
Adjustable slice thickness (in mm)	9 to 18	9 to 12	9 to 18	9 to 12
Loaf pusher height	Low, normal, high	normal	Low, normal, high	normal
OPTIONS				
Wheeled base	•	•	•	•
Auto-start and auto-open safety cover	•	•	standard	standard

STANDARD COLOURS

RAL 9010

RAL 3013

RAL 9005

RAL 9006

RAL 1015

DIMENSIONS (mm)

