1G1PD1G
GAS DIRECT HEATED BOILING PAN, 60 LT.

RANGE FEATURES

Top: 18-10 stainless steel (12/10 mm gauge)
Free-standing structure with top, front panels, sides and control consoles in 18-10 stainless steel; back panels in stainless steel.
Top, sides, back, front panels and control consoles with satin scotchbrite finish.
Side-by-side top configurations with secure fixing between units.
IPX5 protection rating on all units.
CE approval of all gas products.



FUNCTIONAL FEATURES

- Worktop incorporating the boiling pan, fully weld-sealed to the worktop, with condensation collection rim/drainage outlet.
- Rear-hinged spring-loaded lid, in tubolar stainless steel with heat-resistant plastic handle.
- Cylindrical boiling pan with satin finish base and walls to RA 0.6 micron for easy cleaning.
- Pan dimensions: Ø 440x423h mm.
- Direct heating by a group of tubolar stainless steel burners, pilot flame, thermocouple and safety valve.
- Hot and cold water taps on the control panel with adjustable water spout for filling and washing the pan; 2" chromium-plated brass drain tap with heat-resistant knob.
- Safety unit prevents pan operating without water.
- Access to all parts from both the front and the control panel.
- Heat-resistant knobs with screen printed markings and reference index printed on control console.
- Totally sealed flue mounted on the top.
- Height adjustable floor-mounted feet in 18-10 stainless steel - floor clearance 180 mm, with non-scratch sole in insulating plastic material.
- The pan can be equipped with: one section pasta cooker basket in 18-10 stainless steel.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

TECHNICAL FEATURES

- Pan capacity (at 40 mm from the rim): 56 litres.
- Rated output 12 kW.
- Burner spark ignition with protected button.
- Gas supply by 1 group of burners controlled by safety valves.

Width	**Cm**	**70**	**Gas Power**	**kW**	**12 - kcal/h 10.320 - BTU 40,944**
Depth	**Cm**	**70**			
Height	**Cm**	**90**			
Net weight	**Kg**	**75**	**Standard connection**	**V-Hz**	**.**